

NHH 3D Printing



Specification

Product Name:	NPLK20M1
Resin Family:	Carbon Fiber-reinforced PC Compound
Filament Diameter:	1.75mm (±0.03mm)
Melting Point:	230-250°C
Printing Temperature:	240-280°C
Platform Temperature:	90-100°C
Net Weight:	1kg/spool
Color:	Natural Carbon Black, Custom-made
Feature:	Carbon Fiber-reinforced High Stiffness Less Susceptible to Warpage



NHH 3D Printing



規格

產品名稱:	NPLK20M1
基材類別:	碳纖增強聚碳酸酯混合物 (PC-CF)
線徑:	1.75mm (±0.03mm)
熔點:	230-250°C
列印溫度:	240-280°C
熱床溫度:	90 至 100°C (密封式)
淨重:	1kg/卷
顏色:	原碳黑、訂制
特點:	碳纖增強 高剛性 低翹曲



NHH 3D Printing

NHH 3D Printing



规格

产品名称:	NPLK20M1
基材类别:	碳纤增强聚碳酸酯混合物 (PC-CF)
线径:	1.75mm (±0.03mm)
熔点:	230-250°C
打印温度:	240-280°C
热床温度:	90 至 100°C (密封式)
净重:	1kg/卷
颜色:	原碳黑、订制
特点:	碳纤增强 高刚性 低翘曲



NHH 3D Printing